

GRANUDOS

SIMPLY GENIUS.

GRANUDOS 45/100-S5

FUNCTION DESCRIPTION

Chlorine dosing directly from the delivery drum. Acid is dosed into the system directly from the canister to correct the pH and to avoid scaling. Chlorine and acid are dosed separately at intervals to the dissolving system and dissolved completely. Then the chlorine solution is conveyed by a venturi nozzle to the pool water. Dosing manually or linked to an external control system. All functions are permanently monitored.

SCOPE OF DELIVERY

Vertical support: Rotating drum carrier steel, zinc and blue powder coated, drum fixing device with clamp bands and safety belt

Chlorine dosing: Dosing hopper to be screwed on the chemical drum. Dosing motor, dosing screw, knocker to support the dosing. Capacitive switch for empty monitoring of the drum

Acid dosing: Peristaltic dosing pump, suction lance with empty report of the canister, dosing valve 3/8" in the dissolving system

Dissolving system: Pre-filter d 75, flushing tank, booster pump app. 1000 l/h at 1.2 bar, venturi, mixing cyclone. Monitoring of the pump by pressure switch. Monitoring of the suction performance of the venturi. Level monitoring of the flushing tank

Micro processor controller S5: Operation and visualisation via 5-line LC display and three buttons. Fault indications are displayed in plain text. Stepless adjustment of dosing performances chlorine and acid. External dosing control with controllers for free chlorine and pH-value with non-volt contact or 230 V/AC impulse length controlled or frequency. Relay system to assure dosing of only chlorine or acid or none. Switch-off of the dosing at malfunction.



TECHNICAL DATA

Electrical supply	230 V / AC 50 Hz
Power supply	0.39 kW
Water supply	DN20
Water outlet to injection point	DN20
Measures	W 60 cm x D 70 cm x H 140 cm
Weight	app. 50 kg
Dosing performance chlorine	GR45: 0.1 - 2 kg/h GR100: 0.4 - 4 kg/h
Dosing performance acid	3 l/h
Pre-pressure min.	0.2 bar
Back-pressure max.	1.2 bar

TO BE PROVIDED BY THE BUILDER

- Power supply
- Supply tubing and tubing to the injection point
- Overflow/drain in the plants room
- Autocontrol system to control the dosing of the chemicals

ACCESSORIES / OPTIONS

- Drum lifter for 50 kg-drums